



UT-94

Universal Transmitter Alarm/Trip Module

Masibus Model UT-94 is a 4 wire versatile universal transmitter that isolates & converts wide range of conventional / unconventional process inputs into standard process signals acceptable to commercially off the shelf (COTS) automation products. Signal inverting option is also available. The input circuit can accommodate a variety of input signal levels including bi-directional, reverse, true and live-zero.

A built in 4 digit display facilitates the user to monitor process value and helps in fast configuration and calibration. Model UT-94 enables analog signals to transmit without galvanic connections between the fields to the receiving instrument. This in turn allows ground or reference levels to float up to thousands of volts at its input terminals, and prevents circulating current between differing ground potentials that can contaminate input signal.

Isolation provided by Model UT-94 saves the control system from damage due to accidental application of high voltage or induced voltages on the input signal and in turn avoids wrong output signals to process. Isolation provides a good protection for sensitive system parts against voltage spikes etc.

Model UT-94 offers a wide range of input/ output signal types include mA, mV, V, RTD, TC, Resistance. Built-in transmitter power supply (TPS) can drive field transmitters in case of 4-20mA DC input. It offers excellent accuracy and stability for reliable operation in hostile environments and full isolation safely separates each input channel, each output channel and the power supply.

Model UT-94 is equipped with advanced functions like digital filtering, password setting, input and output protection and square root function for optimum process functionality.

Features

- Compact DIN rail mounting
- Digital Display
- Easy configuration using keys & display
- Micro controller based transmitter
- Measuring Parameters: RTD, TC, mV, V, mA, Ω
- Upto Two Retransmission output
- Two Relay Output (Option)
- Modbus protocol on RS485 (Option)
- Square Root Extraction for Linear input type

Applications

- Industrial process control
- Factory automation
- SCADA
- DAS
- Heat treatment furnaces
- Reheat furnaces
- Ceramic Kilns
- Glass Industry
- Water and waste water control

TECHNICAL SPECIFICATIONS

Input		Power Supply			
Input Type	Thermocouple (E, J, K, T, B, R, S, N), RTD (PT-100), mA ,mV, V & Resistance	Standard	85-265VAC/ 125-300VDC		
Display Range	Refer Table-1	Optional	18-36VDC		
Accuracy	Refer Table-1	Power consumption	< 10 VA		
ADC Resolution	17 bits	Isolation (Withstanding voltage) Between primary terminals* and secondary terminals** : At least 1500 V AC for 1 minute Between secondary terminals** : At least 500 V AC for 1 minute * Primary terminals indicate power terminals and relay output terminals. ** Secondary terminals indicate I/O terminals and Communication Port.			
Display Resolution	0.1 / 1°C	Physical			
Sampling Time	< 75ms	Dimensions (mm)	75(H) x 55(W) x 110(D)		
CJC Error	±2.0 °C Max	Mounting	Din Rail		
Sensor Burnout current	0.5uA	Terminal Cable Size	2.5 mm ²		
RTD excitation current	1mA Approx.	Weight	< 250 grams		
NMRR	> 50 dB	Enclosure Material	ABS		
CMRR	> 120 dB	Enclosure Protection	IP20		
Temp-co	< 100ppm/°C	Environmental			
Input Impedance	> 1MΩ for Voltage, 100Ω for Current	Operating temperature	0 to 55 °C		
Max Voltage	20VDC	Storage temperature	0 to 80 °C		
Display & Keys		Humidity	20 to 95 % RH non-condensing		
Process Value	0.3" Four-digit Seven segment, Red LED	Table 1: Display Range			
Status	Power, RL1, RL2, Tx, Rx	Input Type	Ranges		
Keys	3 keys for configuration, calibration and operation		Accuracy		
Output		Thermocouple	E	-200 to 1000 °C	±0.1% of FS
Relay (Option)			J	-200 to 1200 °C	
Relays	2 Nos.		K	-200 to 1370 °C	
Type	Single Change over (C, NO, NC)		T	-200 to 400 °C	
Rating	2A @ 230VAC / 30VDC		N	-200 to 1300 °C	
AO1			R	0 to 1750 °C	±0.25% of FS
Output Signal	4-20mA/ 0-20mA @ 750Ω Max. 1-5VDC/ 0-5VDC/ 0-10VDC @ 4KΩ Min.	S	0 to 1750 °C		
Output accuracy	±0.25% of span	B	450 to 1800 °C	±0.1% of FS	
Temp-co	< 150ppm/°C	RTD Pt-100	-199.9 to 850 °C		
AO2 (Option)		Voltage	-10 to 500mV	-1999 to 9999	±0.1% of FS
Output Signal	4-20mA/ 0-20mA @ 750Ω Max. 1-5VDC/ 0-5VDC/ 0-10VDC @ 4KΩ Min.		0/0.4 to 20mV		
Output accuracy	±0.25% of span		0 to 5V		
Temp-co	< 150ppm/°C		1 to 5V		
Communication (Option)		0 to 10V			
Interface	RS485 (2 Wire)	Current	0/4 to 20mA		
Protocol	Modbus-RTU	Resistance	0 to 2000Ω		
Baud rate	4800, 9600, 19200				
Transmitter Power Supply	24VDC (±1V) @30mA				

Ordering Code

Model	Input Type	APS	No of O/P	O/P type-1	O/P type-2	Relay o/p	Communication
UT-94	X	XX	X	X	X	X	X
	1 E	U1 85-265 VAC/ 125-300 VDC	1 One	1 4-20mA	0 None	N None	N None
	2 J	U2 18-36 VDC	2 Two	2 0-20mA	1 4-20mA	Y Yes	Y RS485
	3 K			3 1-5VDC	2 0-20mA		
	4 T			4 0-5VDC	3 1-5VDC		
	5 B			5 0-10VDC	4 0-5VDC		
	6 R			S Special	5 0-10VDC		
	7 S				S Special		
	8 N						
	9 Pt-100						
	C 4-20 mA						
	D 0-20 mA						
	E 1-5 VDC						
	F 0-5 VDC						
	G 0-10 VDC						
	W 0.4-2 VDC						
	X -10-500 mV						
	Y 0-2 V						
	Z 0-2000 Ohms						
	S Special						